SE Water

OPTOD : OPTICAL DISSOLVED OXYGEN

RANGE DIGISENS / DATASHEET

NEW : exist in Titanium version

Water & Air

APPLICATIONS

- Urban waste water treatment
- Industrial effluent treatment
- Surface Water monitoring
- Sea Water monitoring, fish farming, aquarium
- Drinking Water

OPTICAL TECHNOLOGY

The OPTOD (Optical Dissolved Oxygen technology) is based on luminescent optical technology. The OPTOD sensor is approved by the ASTM International Method D888-05

Without calibration requirements and thanks to an ultra low power technology the OPTOD sensor meets the demands of field works and short or long term campaigns.

Without oxygen consumption, this technology allows you an accurate measure in all situation and especially in very low oxygen concentrations

DIGITAL TECHNOLOGY

The "smart" OPTOD sensor stores calibration and history data within the sensor. This allows you a plug and play system without re-calibration.

Thanks to the universal Modbus RS485 protocol, the SE OPTOD can be connected to all devices commonly used (Datalogger, Controller, Automat, Remote System...).

TECHNICAL CHARACTERISTICS

Measures	
Measure principle	Optical measure by luminescence
Measure ranges	0,00 to 20,00 mg/L
	0,00 to 20,00 ppm
Resolution	0.01
Accuracy	+/-0,1mg/L
	+/-0,1 ppm +/-1 %
Response time	90%of the value in less than 60 seconds
requency of recommended measure	> 5 \$
Water move	No necessary move
Temperature	Via NTC
compensation	
Stocking temperature	-10° C to + 60°C
Sensor	
Dimensions	Diameter : 25 mm ; Length : 146 mm
Weight	Stainless steel version 450g(sensor +cable 3 m) Titanium version 300 g(sensor +cable 3m)
Material	Stainless steel 316L, New : body In Titanium
Maximum pressure	5 bars
Connection	9 armoured connectors, polyurethane jacket, barewires
Protecion	
DIMENSIONS (in mm)	
Authorised Indian C	hannel Partner Local Delears
~ -	
SUN ENVIRONME	NT
Vadodara, Gujarat, India.	
salos@supopuiropmont.com	
M : +91 - 9327557779	
(Time 9.30am to 5.30pm)	